



Issue Date: 27-Oct-2009 Revision Date: 31-Aug-2018 Version 1

1. IDENTIFICATION

Product identifier

Product Name Poly-Glass 320 High Gloss White

Other means of identification

SDS # NAP00083

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended UseUsed for kitchen and bath refinishing.

Details of the supplier of the safety data sheet

Manufacturer Address

North America Polymer Company, Ltd.

7315 Hamlin Ave Skokie, IL 60076 USA

Emergency telephone number

Company Phone Number 800-888-1081 / 847-779-6464

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White liquid Physical state Liquid Odor Slight aromatic odor

Classification

The classification and labeling information in this Safety Data Sheet should be viewed as provisional, as physical test data has not been performed.

Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Signal Word Danger

Hazard statements

May cause respiratory irritation. May cause drowsiness or dizziness Highly flammable liquid and vapor





Revision Date: 31-Aug-2018

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof equipment

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a poison center or doctor/physician if you feel unwell In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Proprietary acetate 1	Proprietary	15-30
Proprietary acetate 2	Proprietary	15-30
Proprietary dioxide	Proprietary	1-10

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Seek immediate medical attention if adverse effect occurs.

Skin Contact Remove exposed or contaminated clothing, taking care not to contaminate eyes.

Immediately begin flushing skin continuously for a minimum of 15 minutes. Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse. Seek

immediate medical attention if adverse effect occurs.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If necessary, use artificial respiration to support vital functions. Call a physician if

you feel unwell.

, . .

Ingestion Give water to conscious/alert person. Do NOT induce vomiting. Call a physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms May cause dermatitis or irritation in some individuals upon prolonged contact. Breathing

mists may cause dizziness and pulmonary irritation. Excessive inhalation may produce dizziness, nausea, headache, and incoordination. May be harmful in contact with skin. May

Revision Date: 31-Aug-2018

cause drowsiness or dizziness. May cause respiratory irritation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Exposure may aggravate pre-existing respiratory or skin problems.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small fires: Dry chemical, CO2, water spray, or regular foam. Large fires: Water spray, fog, or regular foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. May be ignited by heat, sparks or flames. Vapors may travel to source of ignition and flash back. Container may explode in heat or fire. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Explosion Data

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective equipment and precautions for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from heads of containers that have been exposed to intense heat or flame. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. If runoff from the fire control occurs, notify the appropriate authorities. Vapors may travel to source of ignition and flash back.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). In

case of a spill, clear the affected area and protect people. Wear suitable gloves, goggles

and apron.

For Emergency Responders Full-body chemical protective clothing is recommended for emergency response

procedures.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for

additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment For small spills, absorb on polypads or other suitable non-reactive absorbent materials. For

large spills, dike far ahead of spill for later disposal. Absorb with materials such as:

non-combustible material, cat litter / sand.

, .

Methods for Clean-Up

Use clean non-sparking tools to collect absorbed material. Sweep up and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

Revision Date: 31-Aug-2018

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing. Discard shoes that become saturated with product. Wash thoroughly with soap and water after handling. When using do not eat, drink or smoke. Keep container tightly closed. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Ground container and transfer equipment to eliminate static electric sparks. Never use a a torch to cut or weld on or near a container.

Conditions for safe storage, including any incompatibilities

Storage ConditionsStore in a cool, well-ventilated area, away from ignition sources and incompatible materials.

Keep container tightly closed. Store locked up.

Incompatible Materials Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Proprietary acetate 1	STEL: 150 ppm	TWA: 200 ppm	IDLH: 1500 ppm
	TWA: 50 ppm	TWA: 950 mg/m ³	TWA: 200 ppm
		(vacated) TWA: 200 ppm	TWA: 950 mg/m ³
		(vacated) TWA: 950 mg/m ³	_
Proprietary dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
		(vacated) TWA: 10 mg/m ³ total	TWA: 2.4 mg/m ³ CIB 63 fine
		dust	TWA: 0.3 mg/m ³ CIB 63
			ultrafine, including engineered
			nanoscale

Appropriate engineering controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS. For operations where contact can occur, a safety

shower and an eye wash facility should be available.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Splash goggles or safety glasses. Refer to 29 CFR 1910.133 for eye and face protection

regulations.

Skin and Body Protection Chemical resistant, impermeable gloves. Use body protection appropriate for task. An

apron or other impermeable body protection is suggested. Refer to 29 CFR 1910.138 for

appropriate skin and body protection.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. Use NIOSH/MSHA approved

respiratory protection equipment when airborne exposure limits are exceeded.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before

eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before

Revision Date: 31-Aug-2018

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

AppearanceWhite liquidOdorSlight aromatic odorColorWhiteOdor ThresholdNot determined

Property Values Remarks • Method

pH Not determined

Melting point / freezing pointNot availableBoiling point / boiling rangeNot availableFlash point4 °C / 39.2 °F

Evaporation Rate >1 N-butyl acetate

Flammability (Solid, Gas) Not determined

Flammability Limit in Air

Upper flammability or explosive Not determined

limits

Lower flammability or explosive Not determined

limits

Vapor Pressure Not determined

Vapor Density > 1.0 (Air=1)

Relative Density 1.31 Water Solubility negligible Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** 1200 cP **Explosive Properties** Not determined **Oxidizing Properties** Not determined

Other information

VOC Content 1.77 lb/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid all possible sources of ignition.

Incompatible materials

Incompatible with oxidizing agents.

Hazardous decomposition products

Carbon dioxide (CO2). Carbon monoxide. Oxides of sulfur.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact May cause temporary irritation on eye contact.

Skin Contact May be harmful in contact with skin. Prolonged contact may cause redness and irritation.

Inhalation May cause respiratory irritation. May cause drowsiness or dizziness. Breathing of high

concentrations may cause dizziness, light-headedness, headache, nausea and loss of

Revision Date: 31-Aug-2018

coordination.

Ingestion Ingestion may cause irritation to mucous membranes.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Proprietary acetate 1	= 4100 mg/kg (Rat)	> 2 g/kg (Rabbit) > 2000 mg/kg (> 2230 mg/m ³ (Rat) 4 h > 9482
		Rabbit)	mg/m³ (Rat)4 h
Proprietary acetate 2	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
Proprietary dioxide	> 10000 mg/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Proprietary dioxide		Group 2B		X

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document ...

 ATEmix (oral)
 9,659.08 mg/kg

 ATEmix (dermal)
 5,400.30 mg/kg

12. ECOLOGICAL INFORMATION

Revision Date: 31-Aug-2018

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Propylene glycol monomethyl ether		161: 96 h Pimephales promelas	500: 48 h Daphnia magna mg/L
acetate		mg/L LC50 static	EC50
108-65-6			
t-Butyl Acetate		296 - 362: 96 h Pimephales	
540-88-5		promelas mg/L LC50 flow-through	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Proprietary acetate 1	1.38
Proprietary acetate 2	0.43

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of WastesWhatever cannot be saved for recovery or recycling should be managed in an appropriate

and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance

with federal, state and local requirements.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for limited quantity exception.

DOT

UN/ID No UN1263
Proper Shipping Name Paint
Hazard class 3
Packing Group II

IATA

UN number UN1263
Proper Shipping Name Paint
Transport hazard class(es) 3
Packing Group II

Revision Date: 31-Aug-2018

IMDG

UN numberUN1263Proper Shipping NamePaintTransport hazard class(es)3Packing GroupII

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Proprietary acetate 1	Х	Х	Х	Х	Х	Χ	Х	Х
Proprietary acetate 2	Х	Х	Х	Х	Х	Х	Х	Х
Proprietary dioxide	Х	Х	Χ	Χ	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Proprietary acetate 1	5000 lb		RQ 5000 lb final RQ
			RQ 2270 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

SARA 313

Not determined

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Proprietary acetate 1				X

Revision Date: 31-Aug-2018

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Proprietary dioxide -	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Proprietary acetate 1	X	Х	Х
Proprietary dioxide	Х	X	X

16. OTHER INFORMATION

Health Hazards Special Hazards NFPA **Flammability** Instability Not determined Not determined Not determined Not determined HMIS **Health Hazards Flammability** Physical hazards **Personal Protection** Not determined Not determined Not determined Not determined

Issue Date:27-Oct-2009Revision Date:31-Aug-2018Revision Note:New formula

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet