NAPCO

Safety Data Sheet

Issue Date: 08-Mar-2017 Revision Date: 24-Nov-2017 Version 1

1. IDENTIFICATION

Product Identifier

Product Name Poly-Glass Color Dispersions - Blue

Other means of identification

SDS # NAP00071

Product Code 4034 UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Tint. Colorant.

Details of the supplier of the safety data sheet

Manufacturer Address

North America Polymer Company, Ltd.

7315 Hamlin Ave Skokie, IL 60076 USA

Emergency Telephone Number

Company Phone Number 800-888-1081 / 847-779-6464

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Blue liquid Physical state Liquid Odor Slight

Classification

The classification and labeling information in this Safety Data Sheet should be viewed as provisional, as the product's ingredients and percentages are kept as a trade secret / proprietary.

Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3

Hazards Not Otherwise Classified (HNOC)

Causes mild skin irritation

Signal Word Danger

Hazard statements

Suspected of causing cancer
May damage fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure
Flammable liquid and vapor



Revision Date: 24-Nov-2017



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

NOTE: Acute Toxicity classifications are approximates, due to proprietary ingredient percentages.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Xylene	1330-20-7	1-3
Proprietary Pigment	Proprietary	Proprietary
Ethylbenzene	100-41-4	0.3-1.0
2-Methoxypropyl-1-acetate	70657-70-4	0.1-0.3

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

First Aid Measures

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Seek immediate medical attention if adverse effect occurs.

Revision Date: 24-Nov-2017

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation persists, call a physician.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison

center if individual's condition declines or if symptoms persist.

Ingestion Do NOT induce vomiting. Drink plenty of water or milk immediately. Never give anything by

mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion

or loss of coordination. Will cause gastrointestinal tract irritation. Depending on the duration

of skin exposure, skin reddening or discomfort may result.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water fog. Alcohol resistant foam.

Unsuitable Extinguishing Media Water jet.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use spark-proof tools and explosion-proof equipment. Container explosion may occur under fire conditions. Use water spray to keep containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions In case of a spill, clear the affected area and protect people. Wear protective clothing as

described in Section 8 of this safety data sheet. ELIMINATE all ignition sources (no

smoking, flares, sparks or flames in immediate area).

For Emergency Responders Full-body chemical protective clothing is recommended for emergency response

procedures.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Stop leak if you can do it without risk. For small spills, absorb on polypads or other suitable

non-reactive absorbent materials.

Methods for Clean-Up

Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and

shovel into suitable containers for disposal. Discard any product, residue, disposable

Revision Date: 24-Nov-2017

container or liner in full compliance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not breathe vapors or

spray mist. Ground/bond container and receiving equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from

heat, sparks, flame. Store locked up.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	

Appropriate engineering controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS. Maintain eye wash fountain and quick-drench

facilities in work area.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Splash goggles or safety glasses.

Skin and Body Protection Wear protective gloves and protective clothing. Use body protection appropriate for task. An

apron or other impermeable body protection is suggested. Full-body chemical protective

Revision Date: 24-Nov-2017

Slight

clothing is recommended for emergency response procedures.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before

eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before

Odor

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical stateLiquidAppearanceBlue liquid

Color Blue Odor Threshold Not determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH Not determined
Melting Point/Freezing Point Not determined
Boiling Point/Boiling Range Not determined
Flash Point 43 °C / 109.4 °F
Evaporation Rate Not determined
Flammability (Solid, Gas) Not determined

Flammability Limits in Air

Upper Flammability Limits
Lower Flammability Limit

Vapor Pressure
Vapor Density

Not determined
Not determined
Not determined
Not determined

Relative Density 1.11

Water Solubility Not determined Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

Other Information

Density 9.28 lbs/gal

10. STABILITY AND REACTIVITY

Revision Date: 24-Nov-2017

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Heat, flames and sparks.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Moderately irritating to the eyes.

Skin Contact Causes mild skin irritation. Prolonged contact may cause redness and irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion May cause discomfort if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

....

Revision Date: 24-Nov-2017

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity Not determined.

Carcinogenicity Suspected of causing cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity May damage fertility or the unborn child.

Developmental toxicity Not determined.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Unknown Acute Toxicity NOTE: Acute Toxicity classifications are approximates, due to proprietary ingredient

percentages. 87,500.00 mg/kg

 ATEmix (oral)
 87,500.00 mg/kg

 ATEmix (dermal)
 35,814.00 mg/kg

 ATEmix (inhalation-dust/mist)
 37.50 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene		30.26 - 40.75: 96 h Poecilia	3.82: 48 h water flea mg/L EC50
1330-20-7		reticulata mg/L LC50 static 780: 96	0.6: 48 h Gammarus lacustris mg/L
		h Cyprinus carpio mg/L LC50 13.1 -	LC50
		16.5: 96 h Lepomis macrochirus	
		mg/L LC50 flow-through 19: 96 h	
		Lepomis macrochirus mg/L LC50	
		13.4: 96 h Pimephales promelas	
		mg/L LC50 flow-through 23.53 -	
		29.97: 96 h Pimephales promelas	
		mg/L LC50 static 2.661 - 4.093: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 13.5 - 17.3:	
		96 h Oncorhynchus mykiss mg/L LC50 7.711 - 9.591: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		macrocrinus mg/L LC50 static	

Ethylbenzene	438: 96 h Pseudokirchneriella	9.6: 96 h Poecilia reticulata mg/L	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 4.6: 72 h	LC50 static 11.0 - 18.0: 96 h	EC50
	Pseudokirchneriella subcapitata	Oncorhynchus mykiss mg/L LC50	
	mg/L EC50 2.6 - 11.3: 72 h	static 32: 96 h Lepomis macrochirus	
	Pseudokirchneriella subcapitata	mg/L LC50 static 7.55 - 11: 96 h	
	mg/L EC50 static 1.7 - 7.6: 96 h	Pimephales promelas mg/L LC50	
	Pseudokirchneriella subcapitata	flow-through 4.2: 96 h	
	mg/L EC50 static	Oncorhynchus mykiss mg/L LC50	
	_	semi-static 9.1 - 15.6: 96 h	
		Pimephales promelas mg/L LC50	
		static	

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Xylene 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.2

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Whatever cannot be saved for recovery or recycling should be managed in an appropriate

and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance

Revision Date: 24-Nov-2017

with federal, state and local requirements.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethylbenzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

Revision Date: 24-Nov-2017

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT In non-bulk packages, this product is not regulated for ground transportation in

accordance with 49 CFR 173.150(f).

UN/ID No UN1263

Proper Shipping Name Paint related material

Hazard Class 3
Packing Group III

IATA

UN/ID No UN1263

Proper Shipping Name Paint related material

Hazard Class 3
Packing Group III

IMDG

UN/ID No UN1263

Proper Shipping Name Paint related material

Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E	ENCS	IECSC	KECL	PICCS	AICS
			LINCS					
Xylene	Χ	Х	Х	Present	Х	Present	Х	Χ
Ethylbenzene	Χ	Х	Х	Present	Х	Present	Х	Х
2-Methoxypropyl-1-acetate		Х	Х		Х	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

...,

Revision Date: 24-Nov-2017

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardYesSudden Release of Pressure HazardNoReactive HazardNo

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	1-3	1.0
Ethylbenzene - 100-41-4	100-41-4	0.3-1.0	0.1

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			Χ
Ethylbenzene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene	X	X	X
1330-20-7			
Ethylbenzene	X	X	X
100-41-4			

16. OTHER INFORMATION

NFPA_	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date:08-Mar-2017Revision Date:24-Nov-2017Revision Note:Logo Change

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet