



Safety Data Sheet

Issue Date: 17-Mar-2010

Revision Date: 09-Dec-2017

Version 2

1. IDENTIFICATION

Product Identifier

Product Name Regular Dry Poly-Glass High Gloss Clear

Other means of identification

SDS # NAP00055

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Used for kitchen and bath refinishing.

Details of the supplier of the safety data sheet

Manufacturer Address

North America Polymer Company, Ltd.
7315 Hamlin Ave
Skokie, IL 60076 USA

Emergency Telephone Number

Company Phone Number 800-888-1081 / 847-779-6464
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White liquid, clear or pigmented liquid

Physical state Liquid

Odor Aromatic

Classification

Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

Signal Word

Danger

Hazard statements

Causes skin irritation
Suspected of causing cancer
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor



Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Use explosion-proof equipment

Precautionary Statements - Response

- If exposed or concerned: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- If skin irritation occurs: Get medical advice/attention
- In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

- Store locked up
- Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

- Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Propylene glycol monomethyl ether acetate	108-65-6	35-40
Trade Secret	Proprietary	15-20
Xylenes (o-, m-, p- isomers)	1330-20-7	10-15
Ethylbenzene	100-41-4	1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

The product contains 15-20% of a proprietary solvent blend.

4. FIRST AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention if adverse effect occurs.
Skin Contact	Remove exposed or contaminated clothing, taking care not to contaminate eyes. Immediately begin flushing skin continuously for a minimum of 15 minutes. Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse. Seek immediate medical attention if adverse effect occurs.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If necessary, use artificial respiration to support vital functions. Call a physician if you feel unwell.
Ingestion	Give water to conscious/alert person. Do NOT induce vomiting. Call a physician immediately.

Most important symptoms and effects

Symptoms	May cause severe eye irritation with reddening and watering. May cause dermatitis or irritation in some individuals upon prolonged contact. Breathing mists may cause dizziness and pulmonary irritation. Excessive inhalation may produce dizziness, nausea, headache, and incoordination. May be harmful in contact with skin.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Exposure may aggravate pre-existing respiratory or skin problems.
---------------------------	---

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small fires: Dry chemical, CO₂, water spray, or regular foam. Large fires: Water spray, fog, or regular foam.

Unsuitable Extinguishing Media Water jet.

Specific Hazards Arising from the Chemical

Flammable/combustible materials. May be ignited by heat, sparks or flames. Vapors may travel to source of ignition and flash back. Container may explode in heat or fire. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂). Oxides of sulfur.

Explosion Data

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective equipment and precautions for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from heads of containers that have been exposed to intense heat or flame. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. If runoff from the fire control occurs, notify the appropriate authorities. Vapors may travel to source of ignition and flash back.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). In case of a spill, clear the affected area and protect people. Wear suitable gloves, goggles and apron.

For Emergency Responders Full-body chemical protective clothing is recommended for emergency response procedures.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment For small spills, absorb on polypads or other suitable non-reactive absorbent materials. For large spills, dike far ahead of spill for later disposal. Absorb with materials such as: non-combustible material, cat litter / sand.

Methods for Clean-Up Use clean non-sparking tools to collect absorbed material. Sweep up and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Never use a torch to cut or weld on or near a container.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, well ventilated area away from acids and other incompatible substances. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible Materials Incompatible with oxidizing agents. No information available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Trade Secret	STEL: 150 ppm TWA: 50 ppm	TWA: 200 ppm TWA: 950 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m ³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Appropriate engineering controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. For operations where contact can occur, a safety shower and an eye wash facility should be available.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Splash goggles or safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear neoprene or butyl rubber gloves for routine industrial use. Use body protection appropriate for task. An apron or other impermeable body protection is suggested. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standard (29CFR 1910.134), applicable U.S. State regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

General Hygiene Considerations Take off all contaminated clothing and wash it before reuse. Avoid contact with skin, eyes or clothing. After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Aromatic
Appearance	White liquid, clear or pigmented liquid	Odor Threshold	Not determined
Color	White Clear		

Property	Values	Remarks • Method
pH	Not determined	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	Not determined	
Flash Point	4 °C / 39 °F	
Evaporation Rate	>1	
Flammability (Solid, Gas)	Not determined	
Flammability Limits in Air		
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	1.29	
Water Solubility	Negligible	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Avoid all possible sources of ignition.

Incompatible Materials

Incompatible with oxidizing agents. No information available.

Hazardous Decomposition Products

Carbon dioxide (CO₂). Carbon monoxide. Oxides of sulfur.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

May cause moderate eye irritation.

Skin Contact

Causes skin irritation. May be harmful in contact with skin.

Inhalation

Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination.

Ingestion

Ingestion may cause irritation to mucous membranes.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Suspected of causing cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylenes (o-, m-, p- isomers) 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

Legend

- ACGIH (American Conference of Governmental Industrial Hygienists)*
- A3 - Animal Carcinogen*
- IARC (International Agency for Research on Cancer)*
- Group 2B - Possibly Carcinogenic to Humans*
- Group 3 IARC components are "not classifiable as human carcinogens"*
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)*
- X - Present*

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Chronic toxicity Xylene vapors are harmful! Overexposure to high concentrations can cause eye, nose, throat, lung irritation; CNS (brain) effects: dizziness, difficulty in breathing, unconsciousness, coma and death. Reports of heart irregularities from massive exposures. Prolonged overexposures can cause brain, liver, kidney effects/damage. Skin: can be absorbed. Repeated/Prolonged contact is irritating. Eyes: Irritant. Oral: harmful or fatal if swallowed. Pulmonary aspiration hazard-can enter lungs and cause damage. In rats, prolonged breathing of 500 ppm - fetal effects but no birthdefects: No effects at 400 ppm. High oral dose was toxic to pregnant mice; cleft palate in fetuses.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

- ATEmix (oral)** 7,081.00 mg/kg
- ATEmix (dermal)** 3,433.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Propylene glycol monomethyl ether acetate 108-65-6 Trade Secret		161: 96 h Pimephales promelas mg/L LC50 static 296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	500: 48 h Daphnia magna mg/L EC50
Xylenes (o-, m-, p- isomers) 1330-20-7		780: 96 h Cyprinus carpio mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

Ethylbenzene 100-41-4	438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	macrochirus mg/L LC50 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
--------------------------	--	---	---

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Propylene glycol monomethyl ether acetate 108-65-6	0.43
Trade Secret	1.38
Xylenes (o-, m-, p- isomers) 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.2

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylenes (o-, m-, p- isomers) 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for limited quantity exception.

DOT

UN/ID No UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II

IATA

UN/ID No UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II

IMDG

UN/ID No UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Propylene glycol monomethyl ether acetate	X	X	X	Present	X	Present	X	X
Trade Secret	X	X	X	Present	X	Present	X	X
Xylenes (o-, m-, p- isomers)	X	X	X	Present	X	Present	X	X
Ethylbenzene	X	X	X	Present	X	Present	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Trade Secret	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers) - 1330-20-7	1330-20-7	10-15	1.0
Ethylbenzene - 100-41-4	100-41-4	1-5	0.1

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Trade Secret				X
Xylenes (o-, m-, p- isomers)	100 lb			X
Ethylbenzene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Trade Secret	X	X	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards 3	Flammability 4	Instability 0	Special Hazards Not determined
<u>HMIS</u>	Health Hazards Not determined	Flammability Not determined	Physical hazards Not determined	Personal Protection Not determined

Issue Date: 17-Mar-2010
Revision Date: 09-Dec-2017
Revision Note: Regulatory update Section 2 update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet